

Reciprocating Saw

JR3061T

1 250 W • 0 – 3 000 min⁻¹ • 32 mm

Rugged reciprocating saw with three-stage pendulum action

A basic reciprocating saw for spark-free cutting of metal and demolition work. An efficient 1 250 W motor, stroke length of 32 mm and stroke rate of 0 – 3 000 min⁻¹ with continuous control from the switch. Three-stage pendulum action and quick-release blade attachment.



■ Technical specifications

Continuous Input Power	1250 W
Strokes per Minute (SPM)	0 - 3000 min ⁻¹
Length of Stroke	32 mm
Max. Cutting Capacity in Wood (90°)	255 mm
Max. Cutting Capacity in Steel Pipe	130 mm
Power Supply Cord	2,5 m
Sound Power Level (L _{WA})	99 dB(A)
Sound Pressure Level (L _{pA})	88 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Weight Without Cable	3,8 kg
Product Dimensions (L x W x H):	487 x 95 x 177 mm
Vibration Level, Cutting Boards	18,5 m/s ²
Vibration Level, Cutting Wooden Beam	16,5 m/s ²
Vibration Uncertainty (K Factor), Cutting Boards	1,5 m/s ²
Vibration Uncertainty (K Factor),	2,0 m/s ²

■ **EAN 0088381867009**

Link to product - www.makita.com



Related products

Optional AC

821718-8

Plastic Carrying Case



B-05038

Reciprosaw Blade 152 x 0,9 mm



B-05044

Reciprosaw Blade 152 x 0,9 mm



B-05153

Reciprosaw Blade 203 x 1,0 mm



B-13677

Reciprosaw Blade Set 3 pcs



B-55566

Reciprosaw Blade 100 x 1,25 mm



B-55572

Reciprosaw Blade 152 x 1,25 mm



B-55572-10

Reciprosaw Blade 152 x 1,25 mm



B-55588

Reciprosaw Blade 228 x 1,25 mm



B-55588-10

Reciprosaw Blade 228 x 1,25 mm



B-55594

Reciprosaw Blade 305 x 1,25 mm



B-55594-10

Reciprosaw Blade 305 x 1,25 mm



Other

[User manual](#)

[Parts drawing](#)