

Rotary Hammer XGT®

HR004G

40Vmax • SDS-PLUS • 28 mm • 2,9 J

Three-mode, anti-vibration rotary hammer for professionals

Efficient combination hammer delivers high power for professional work. The tool is lightweight and the tool balance is redesigned for increased operability. Equipped with Anti vibration technology (AVT). Counterweight mechanism and vibration absorbing handle to reduce vibration.



Technical specifications

Nominal Battery Voltage	40 V
Voltage XGT	✓
Brushless Motor	✓
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 980 min ⁻¹
Impacts per Minute (IPM)	0 - 5000 min ⁻¹
Max. Drilling Diameter in Wood	32 mm
Max. Drilling Diameter in Concrete	28 mm
Max. Drilling Diameter in Steel	13 mm
Optimum Drilling Diameter Range in Concrete	10 - 18 mm
Impact Energy	2,9 J
Drilling diameter with TCT core bit	54 mm
Electronic brake	✓
Sound Power Level (L _{WA})	104 dB(A)

User benefits

- Impact drilling, non-impact drilling and spike function
- AVT (Anti-Vibration Technology) ensures extra-low vibration performance
- XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions
- Low power consumption thanks to brushless motor
- Constant speed control automatically applies additional power to the motor to maintain speed under load to complete the most challenging jobs
- Quick-release chuck for metal and wood drill bits without impact
- Battery protection circuit protects against overloading, over-discharging and over-heating

[Link to product - www.makita.com](http://www.makita.com)



Related products

Optional AC

191E60-4

Dust Collection System DX14



198993-4

Grease vessel for bit 100 ml



199139-5

Quick Drill Chuck Set 13 Mm, 1/2",



331886-4

Depth Gauge



821552-6

Makpac case (4)



835C84-5

Makpac Inner Tray Type 4



Other

[User manual](#)

[Parts drawing](#)